



Medidas Referenciales / Estimated Dimensions, Acot. mm [pulg.] / Dim. mm [inch.]

## CARACTERÍSTICAS DEL PRODUCTO / PRODUCT FEATURES

Diseño ergonómico de construcción robusta con cerámica de 10mm de espesor, con sistema de descarga Turvex con sifón jet y espejo de agua óptimo, mueble libre de alabeo (base plana).

### MATERIAL:

Cerámica porcelanizada de alto brillo  
Calidad "A", Tipo I

### VÁLVULAS:

Válvula de admisión y descarga certificadas  
Válvula de admisión silenciosa  
Válvulas armadas y calibradas  
Válvula de descarga con sello hermético  
Válvula de descarga de Ø 3" tipo sapo.

### ACCESORIOS:

Sistema de sujeción al piso

### CONEXIÓN:

A la alimentación Ø15/16-14 NS-1  
A la descarga se acopla al Ø de drenaje de 4" con brida sanitaria o cuello de cera

### PRESIÓN DE TRABAJO

Pmin.=0,25 kg/cm<sup>2</sup>  
Pmax.=6,0 kg/cm<sup>2</sup>

### OPERACIÓN:

Accione la Palanca para una descarga de 3,8 litros

### GASTO MÁXIMO:

3,8 lpd  
Los productos ilustrados pueden sufrir cambios sin previo aviso en su aspecto o partes, como resultado de los procesos de mejora continua al que están sujetos, sin implicar mayor responsabilidad de la fábrica.

*Ergonomic design of robust construction with 10mm thick ceramic, with Turvex discharge system with jet siphon and optimal water mirror, free roll unit (flat base).*

### MATERIALS:

*Ceramic high gloss porcelain  
Quality "A", Type I*

### VALVES:

*Certified fill and flush valves  
Silent valve fill  
Valves reinforced and calibrated  
Flush valve with hermetic seal  
Flush valve Ø 3" flapper type.*

### ACCESSORIES:

*Floor fixing kit*

### CONNECTION:

*To the supply Ø15/16-14 NS-1  
Coupling to the drain Ø 4" with toilet flange or wax ring*

### WORKING PRESSURE.

*Pmin.=3,55 psi  
Pmax.=85,34 psi*

### OPERATION:

*Operate the Lever for a 1,0 gallons discharge*

### MAXIMUM CONSUMPTION:

*1,0 gpf*

### GARANTÍA:

Helvex, S. A. de C. V. garantiza sus productos cerámicos como libres de defectos en materiales y procesos de fabricación por 30 años. En los herrajes por defectos de manufactura por 5 años. En el dispositivo TDS en el mingitorio seco por 3 años. Tapa y asiento por un periodo de 2 años. La vigencia de la garantía inicia a partir de la fecha de entrega del producto al consumidor indicada en esta Póliza de Garantía.

### NORMATIVA:

Cumple con la norma NOM-009-CONAGUA-2001 y NOM-010-CONAGUA-2000.

### WARRANTY:

*HELVEX S. A. de C. V. guarantees its chinaware to be free of defects in materials and workmanship for 30 years. 5 years for the seat, cover and fittings. 5 years warranty for the hardware for manufacturing defects. 3 years warranty for the TDS device in the dry urinal. 2 years warranty for the cover and seat. The validity of the guarantee starts from the date of delivery of the product to the consumer indicated in this Guarantee Policy.*

### REGULATIONS:

*NOM-009-CONAGUA-2001  
NOM-010-CONAGUA-2000*

*Illustrated products may suffer changes without previous notice in its appearance or parts, as a result of the continuous improvement processes to which they are subject, does not imply greater responsibility of the factory.*



Asesoría y Servicio Técnico: (52) 55 53 33 94 31  
Consultancy and Technical Service:  
servicio.tecnico@helvex.com.mx



Refacciones Originales: (52) 55 53 33 94 00  
Original Spare Parts: (52) 55 53 33 94 21  
refacciones@helvex.com.mx Ext. 5913, 5068 y 4815